					Material	l Safety Data Sh
		ASD	SR	еро	rt	
Applicant's nar	ne	Shenzhen Le	qi Network Tec	chnology Co.,	Ltd	
Applicant's Ad	dress		501 and 601, B nguang Road,			
Name of Sampl	e	SmallRig VB	99 mini V-mour	nt Battery		
Model		VB99				
Nominal Voltag	e	14.8V	Ċ		C)	
Rated Capacity		6.7Ah, 99.16 [\]	Wh			
Weight		546.5g				
Size (L×W×T)	S	(106.0×72.6×	:52.2)mm		Ś	
Prepared By		2101 & 2201,	CT Testing Tech , Zhenchang Fa ao'an District, S	actory, Rensha	an Industrial Z	
Report No.		TCT221208M	1084			
	Ś				Ś	
Vritten by:	Aboy	mo	Approved	by:	Tomsin	-
						LISTING TECHN
nspected by:	Army	They	Effective	Date:	2023. 01. 01	

Material Safety Data Sheet

TCT通测检测 TESTING CENTRE TECHNOLOGY

Name of Sample	SmallRig VB99 mini V-mou	nt Battery	
Manufacturer's name	SHENZHEN RIHUIDA ELE	CTRONICS CO., LTD	~
Manufacturer's Address	Bldg 4, Fuzhong Industrial F	Park, FuYong, Bao'an Distr	ict, Shenzhen
Contact Person	Ms. Zhong		
Tel	+86-18820731331		
Emergency Tel	+86-18820731331		3) (2
E-mail	2234384869@qq.com		
Classification of Danger	See section 14.		3) (
Primary Route(s) of Exposure	Eye, skin contact, ingestion.		
	The batteries are not hazardo manufacturer under normal of fire, heat, leakage of internal of including but not limited to the eirquited, put into fire, wheele	onditions. In case of abuse components, which could c	, there's Hazard of rupture, ause casualty loss. Abuses for long time, short
Health Hazard	crushed, and broken.		
Health Hazard			

Chemical Name	Concentration or concentration ranges (9	%) CAS Number
thium Cobalt Oxide	15-40	12190-79-3
Graphite	10-30	7782-42-5
hosphate(1-), hexafluoro-, lithium	10-30	21324-40-3
copper	7-13	7440-50-8
luminum foil	5-10	7429-90-5
lickel	1-5	7440-02-0

Labeling according to EC directives.

No symbol and Hazard phrase are required.

TCT通测检测 TESTING CENTRE TECHNOLOGY

Note: CAS number is Chemical Abstract Service Registry Number.

N/A=Not apply.

Section 4- First Aid Measures

Eye	Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.
Skin	Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get medical aid.
Inhalation	Remove from exposure and move to fresh air immediately. Use oxygen if available.
Ingestion	Ingesting damaged batteries, do not induce vomiting or give food or drink. Seek medical attention immediately.

Section 5- Fire Fighting Measures

Characteristics of Hazard	Dusts at sufficient concentrations can form explosive mixtures with air. Combustion generates toxic fumes.
Hazardous Combustion Products	Carbon dioxide.
Fire-extinguishing Methods and Extinguishing Media	For small fires, use water spray, dry chemical, carbon dioxide or chemical foam.

 Report No.: TCT221208M084
 Page 3 of 8

 Hotline: 400-6611-140
 Tel: 86-755-27673339
 Fax: 86-755-27673332
 http://www.tct-lab.com

	Material Safety Data Sheet
Attention inWear self-contained breadFire-extinguishing(approved or equivalent)	athing apparatus in pressure-demand, MSHA/NIOSH and full protective gear.
Section 6- Accidental Release Meas	sures
Personal Precautions, protective equipment, and emergency procedures	In case of rupture. Attention! Corrosive material. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Refer to protective measures listed in Sections 7 and 8.
Environmental Precautions	Prevent product from contaminating soil and from entering sewers or waterways.
Methods and materials for Containment	Stop the leak if safe to do so. Contain the spilled liquid with dry sand or earth. Clean up spills immediately.
Methods and materials for cleaning up	Absorb spilled material with an inert absorbent (dry sand or earth). Scoop contaminated absorbent into an acceptable waste container. Collect all contaminated absorbent and dispose of according to directions in Section 13. Scrub the area with detergent and water; collect all contaminated wash water for proper disposal.
Section 7- Handling and Storage	
Handling	The battery may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.
Storage	Store in a cool, dry, well-ventilated area away from incompatible substances. Store locked up. Keep out of the reach of children.
	In case of rupture. Handle in accordance with good industrial hygiene and safety practice. Avoid contact
Other Precautions	with skin, eyes or clothing. Use personal protection equipment.
Other Precautions	with skin, eyes or clothing. Use personal protection equipment.

		Material Safety Data Sheet		
Personal Protect	ive Equipment	Eye and Face Protection: None required for consumer use. If there is a Hazard of contact: Tight sealing safety goggles. Face protection shield. Skin and Body Protection: None required for consumer use. If there is a Hazard of contact: Wear protective gloves and protective clothing. Respiratory Protection: No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.		
Section 9- Phy	sical and Chemical P	roperties		
	Appearance: Prismatic			
Physical State	Color: Black			
	Odour: If leaking, smells o	f medical ether.		
Change in condit	tion			
оН	Not applicable as supplied			
Flash Point	Not applicable unless individual components exposed.			
Flammability	Not applicable unless individual components exposed.			
Relative density:	Not applicable unless indiv	Not applicable unless individual components exposed.		
Solubility (water)	Not applicable unless individual components exposed.			
Solubility (other)	Not applicable unless individual components exposed.			
Section 10 – S	tability and Reactivity			
Chemical Stabilit	y	Stable under recommended storage conditions.		
Possibility of Haz	zardous Reactions	None under normal processing.		
Conditions to Ave	oid	Exposure to air or moisture over prolonged periods.		
Incompatible ma	terials	Acids, Oxidizing agents, Bases.		
Hazardous Deco	mposition Products	Carbon oxides.		
)				

Material Safety Data Sheet

Section 11 – Toxicologica	I Information	
Irritation		In the event of exposure to internal contents, vapour fumes may be very irritating to the eyes and skin.
Sensitization		Not Available.
Reproductive Toxicity	S.	Not Available.
Toxicologically Synergistic M	aterials	Not Available.
	40	
Section 12-Ecological Inf	ormation	
General note:	(S)	Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Anticipated behavior of a che in environment/possible envir impact/ ecotoxicity		Not Available.
Section 13 – Disposal Co	nsiderations	Recycle or dispose of in accordance with
Waste Treatment		government, state & local regulations.
Attention for Waste Treatmen	t	Deserted batteries shouldn't be treated as ordinary trash. Shouldn't be thrown into fire or placed in high temperature. Shouldn't be dissected, pierced, crushed or treated similarly. Best disposal method is recycling.
Section 14 – Transport In	formation	
UN number	3480 & 3481	
Proper shipping name	Lithium ion batteries (limited to a maximum of 30% SoC) or; Lithium ion batteries packed with equipment (including lithium ion polymer batteries) or; Lithium ion batteries contained in equipments (including lithium ion polymer batteries).	
Label(s) / Placard Required	Miscellaneous Lithium batt	
		e aware of, or needs to comply with, in er within or outside their premises
Report No.: TCT221208M084 Hotline: 400-6611-140 Tel: 8	36-755-27673339	Page 6 of 8 Fax: 86-755-27673332 http://www.tct-lab.com

	Material Safety Data Sheet
	Can be shipped by air in accordance with International Civil Aviation Organization (ICAO), TI or International Air Transport Association (IATA), DGR Packing Instructions (PI) 965 Section IB, PI 966 Section and PI 967 Section II appropriate of IATA DGR 64 rd (2023 Edition) for transportation.
IMDG CODE:	The batteries are not restricted to IMDG Code 2020 Edition (Amdt 40-20) according to special provision 188.
DOT:	Other requirements for the US Department of Transportation (DOT) Subchapter C, Hazardous Materials Regulations if shipped in compliance with 49 CFR 173.185.
ADR/ ADN:	The batteries are not subject to the provisions of United Nations Economic Commission for Europe (UNECE) ADR/ADN if they meet th requirements of special provision 188 of Chapter 3.3. Applicable as fro 1 January 2021.
tests set out in Subsection 38.	ransport each lithium cell and battery types must have passed the applicable 3 of the UN Manual of Tests and Criteria.
Section 15 – Regulato	bry Information
Dangerous Goods Regulat	ions
	Fransport of Dangerous Goods-Model Regulations (22 nd revised edition) Fransport of Dangerous Goods-Manual of Tests and Criteria
Recommendations on the	
Recommendations on the	Association (IATA)
International Air Transport	Association (IATA) gerous Goods (IMDG Code 2020 Edition Amdt 40-20)
International Air Transport	gerous Goods (IMDG Code 2020 Edition Amdt 40-20)
International Air Transport	gerous Goods (IMDG Code 2020 Edition Amdt 40-20) ne Safe Transport of Dangerous Goods
International Air Transport	gerous Goods (IMDG Code 2020 Edition Amdt 40-20)

Toxic Substance Control Act (TSCA)

Code of Federal Regulations

In accordance with all Federal, State and local laws




Material Safety Data Sheet

Section 16 – Additional Information

MSDS creation date: 2023 Version: 1.0

Sample photo:



To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

The data/information contained herein has been reviewed and approved for general release on the basis that this document contains no export controlled information.

End of report

Shenzhen TCT Testing Technology Co., Ltd. 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China Report Search Number: TCT221208M084 Search System: http://www.tct-lab.com Page 8 of 8